Sanitized Copy Approved for Release 2011/08/09: CIA-RDP89B00487R000300490039-8 81 cc 3/21/27 26 February 1957 Subject: Contract Change Proposal #6, Additional Configuration Mounting Fittings and Locating Jigs for Configuration Mounting Fittings Reference: Contract BC-200 &Dear Sir: Field operations experience and an In-Plant Engineering Support survey, in cooperation with the aircraft people, has indicated the need for a complete set of A-1, A-2 and B Configuration mounting fittings to be permanently assigned to each aircraft. At present, the mounting fittings a peculiar to a configuration type are being supplied with each configuration. The mounting fittings for Configuration B are adjustable to center the cameras over the hatch windows. Once the adjustment is made for a particular aircraft, the setting should remain undisturbed and periodically checked. For Configurations A-1 and A-2 the forward mounting fitting on Bulkhead 252 is permanently installed and is also used for B A Configuration. By assigning a set of configuration mounting fittings to $m \sim$ each aircraft, the need to move fittings from one aircraft to another is o eliminated and the critical adjustments are not disturbed. There is also realized a speed-up of the preflight installation of the configurations and last minute interchangeability of configurations between aircraft. The mounting fittings for Configuration B serve as the basic fitting for Configuration C. Other special fittings, which are required for Configuration C only, are not included. They will be considered at a later date when quantity requirements are more firmly established. A locating jig for the configuration mounting fittings is required for the initial installation of the fittings and to be used for periodic adjustment. The fittings required (including five (5) for FAK and Depot Spares) over and above those presently available or yet to be delivered with configuraportions are as follows: 25X1 Total Total Additional Quantity Quantity Quantity Required Supplied Recommended A Configuration Mounting Fittings B Configuration Mounting Fittings Sanitized Copy Approved for Release 2011/08/09 : CIA-RDP89B00487R000300490039-8

In addition, it is proposed that six (6) locating jigs for the configuration mounting fittings be supplied, one (1) for each of the three (3) detachments, two (2) for FOG, and one (1) for the aircraft factory.

The prime requirement for the locating jig is to establish the critical adjustment and position of the Configuration Mounting Fittings in the equipment bay for the initial adjustment and the required periodic readjustments. The jig will also be designed to perform an essential function in boresighting Configuration C and the Drift Sight.

It is recommended, therefore, that the referenced contract be amended to include the following:

	Quantity	Unit Price	Total Price	
1. A Configuration Mounting Fittings	16 ,∢	\$275.00	\$4,400.00	
2. B Configuration Mounting Fittings	12.	320.00	3,840.00	
3. Locating Jigs for Configuration C Mounting Fittings	B & OK	835.00	5,010.00	(ILLEGIB
Delivery will be completed within s	seventy-five	(75) days fro	m approval	3
to proceed.				ILLEGIB

Please advise us of the distribution of above items between Customer A and Customer B.

We trust that this will meet with your approval and request that a contract amendment be issued for a net contract price increase of \$13,250.00.

Very truly yours,

HYCON MFG. COMPANY

25X1

Instrument Division U	
WAS/pe Per Low - 1 set 9 19 0 8 fettings for A C. for Prog. 3 Lits sets 9 c fetting - for Prog. 3 rets breating jugo for 13 0 c fe Prog.	7
Sanitized Copy Approved for Release 2011/08/09 : CIA-RDP89B00487R000300490039-8	,